

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A method for encoding digital information, the method comprising
identifying a target code word that represents at least a portion of the digital information;
determining a set of a plurality of code words, wherein the set includes the target code word; ~~and~~
selecting an index, wherein the index indicates the determined set;
~~determining a check value for the target code word; and~~
~~sending the check value and the index to a decoder, the index allowing~~
~~identification of the set of the plurality of code words and the check value allowing the target~~
~~code word to be determined from the set.~~
2. (Original) The method of claim 1, further comprising
defining a plurality of sets of code words.
3. (Original) The method of claim 2, further comprising
defining a partition of sets of code words.
4. (canceled)
5. (Original) The method of claim 1, wherein the target code word indicates one or more pixel values in digital video information.
6. (Original) The method of claim 1, wherein the target code word indicates a macro block in a frame of digital video information.

7. (Original) The method of claim 1, further comprising quantizing the target code word.

8. (Original) The method of claim 7, wherein the digital information includes digital video information including frames and wherein the target code word is encoded using intra-coding within a given frame of the digital video information.

9. (Original) The method of claim 8, further comprising using motion prediction is used to determine a correlation noise value; and using the correlation noise value to partition a plurality of code word values into a plurality of sets.

10. (Original) The method of claim 1, further comprising transforming at least a portion of the digital information from a spatial domain into a frequency domain.

11. (Original) The method of claim 10, wherein the step of transforming includes a substep of using a discrete cosine transform.

12. (Original) The method of claim 1, further comprising classifying blocks of the digital information for subsequent processing.

13. (Original) The method of claim 12, further comprising skipping encoding a block in response to the step of classifying blocks.

14. (Original) The method of claim 12, further comprising intra-coding a block in response to the step of classifying blocks.

15. (Original) The method of claim 12, further comprising performing varying degrees of encoding in response to the step of classifying blocks.

16. (Original) The method of claim 15, wherein 16 different classifications are used, including skipping, intra-coding and 14 syndrome coding classes.

17. (Currently amended) An apparatus for encoding digital information, the apparatus comprising
a process for identifying a target code word that represents at least a portion of the digital information;

a process for determining a set of a plurality of code words, wherein the set includes the target code word; ~~and~~
a process for selecting an index, wherein the index indicates the determined set;
a process for determining a check value for the target code word; and
a process for sending the check value and the index to a decoder, the index
allowing identification of the set of the plurality of code words and the check value allowing the
target code word to be determined from the set.

18. (Currently amended) A computer-readable medium including instructions for encoding digital information, the computer-readable medium comprising
one or more instructions for identifying a target code word that represents at least a portion of the digital information;

one or more instructions for determining a set of a plurality of code words,
wherein the set includes the target code word; ~~and~~
one or more instructions for selecting an index, wherein the index indicates the determined set;
one or more instructions for determining a check value for the target code word;
and

one or more instructions for sending the check value and the index to a decoder,
the index allowing identification of the set of the plurality of code words and the check value
allowing the target code word to be determined from the set.

19. (Currently amended) A method for decoding encoded digital information, the method comprising

receiving an index and a check value;
using the index to determine a set of candidate code words;
inferring a set of cues;
determining a ~~target~~ code word by operating on the code words in the set of
candidate code words with a cue;
determining if the determined code word is the target code word when a check
value is determined for the code word that corresponds to the received check value; and
using the target code word in a decoding operation.

20. (Currently amended) The method of claim 19, further comprising
determining a cue in the set of cues;
using the cue to determine a code word in the code words in the set; and
determining whether an operation with a cue performed on a the code word
produces a check value that is in agreement with ~~a the received~~ check value.

21. (Original) The method of claim 19, wherein the cue includes a motion-based predictor.

22. (Original) The method of claim 21, wherein the step of inferring a cue includes a substep of
deriving the motion-based predictor.

23. (Original) The method of claim 22, wherein the encoded digital information includes blocks of video information, the method further comprising

decoding the encoded digital information by using the predictor and one or more code words.

24. (Original) The method of claim 23, further comprising
estimating the best way to decode the encoded digital information by using the predictor and the one or more code words.

25. (Currently amended) An apparatus for decoding encoded digital information, the apparatus comprising

a process for receiving an index and a check value;
a process for using the index to determine a set of candidate code words;
a process for inferring a set of cues;
a process for determining a ~~target~~-code word by operating on the code words in the set of the candidate code words with a cue;
a process for determining if the determined code word is the target code word when a check value is determined for the code word that corresponds to the received check value; and
a process for using the target code word in a decoding operation.

26. (Currently amended) A computer-readable medium including instructions for decoding encoded digital information, the computer-readable medium comprising

one or more instructions for receiving an index and a check value;
one or more instructions for using the index to determine a set of candidate code words;
one or more instructions for inferring a set of cues;
one or more instructions for determining a ~~target~~-code word by operating on the code words in the set of the candidate code words with a cue;
one or more instructions for determining if the determined code word is the target code word when a check value is determined for the code word that corresponds to the received check value; and

one or more instructions for using the target code word in a decoding operation.

27. (withdrawn) A method for transferring information, the method comprising using an encoder to generate and send a first stream encoded at a first complexity level to a first decoder; and

using the encoder to generate and send a second stream encoded at a second complexity level to a second decoder.

28. (withdrawn) The method of claim 27, wherein the encoder generates the streams at different complexity levels in response to a signal from a network.

29. (withdrawn) The method of claim 27, wherein the information is transferred over a network, wherein the network includes processing resources, the method further comprising

using the network's processing resources to decode and then encode at least one of the streams prior to receipt of the stream at a decoder.

30. (Original) A method for sharing processing complexity between an encoding process and a decoding process, wherein the encoding process and the decoding process each use an index for a target codeword, a check value for the target codeword and a set of candidate cues, the method comprising

using the encoder to perform the following steps:

selecting some cues from the set of candidate cues;

operating these cues on the indexed set of codewords;

generating a check value as a result of the operating step;

determining whether the check value matches the check value for the target codeword;

signaling whether the chosen cues were successful in determining the correct codeword to the decoder;

using the decoder to perform the following steps:

selecting other cues from the set of candidate cues;
operating these cues on the indexed set of codewords based on the signal
determined by the encoder;
generating a check value as a result of the operating step;
determining whether the result of the operating step produces a value that is in
agreement with the check value for the target codeword

31. (original) The method of claim 30, wherein the encoding process does not use any of a set of candidate cues corresponding to a lower complexity level, wherein the decoding process uses all of a set of candidate cues corresponding to a higher complexity level.

32. (original) The method of claim 30, wherein the encoding process uses all of a set of candidate cues corresponding to a higher complexity level, wherein the decoding process uses one of a set of candidate cues corresponding to a lower complexity level.

33. (original) The method of claim 19, wherein the encoded digital information corresponds to a source that can be compressed by predictive coding, wherein the decoder includes two or more cues that produce a value that is in agreement with the check value to result in successful recovery of the target codeword.